

Gas Quality Specifications

TransCanada and other pipelines



TransCanada Pipelines

Specs	Canadian Mainline	NGTL/ATCO Pipelines	Foothills (BC) Zone 8	Foothills (Sask.) Zone 9	GTN	North Baja	ANR
Hydrogen Sulphide	Max 23 mg/m ³	Max 23 mg/m ³	Max 23 mg/m ³	Max 23 mg/m ³	Max 0.25 grains/Ccf	Max 0.25 grains/Ccf	Max 1 grains/Ccf SE & SW area 1/4 grains/Ccf Mainline area
Total Sulphur	Max 115 mg/m ³	Max 115 mg/m ³	Max 230 mg/m ³	Max 230 mg/m ³	Max 10 grains/Ccf	Max 0.75 grains/Ccf Total, 0.3 grains/Ccf mercaptan	Max 20 grains/Ccf
Carbon Dioxide	Max 2% by volume	Max 2% by volume	Max 2% by volume	Max 2% by volume	Max 2% by volume	Max 2% by volume	Max 2% by volume
Oxygen	Max 0.4% by volume	Max 0.4% by volume	Max 0.4% by volume	Max 0.4% by volume	Max 0.4% by volume	Max 0.2% by volume	Max 1% by volume
Nitrogen	See TCPL Mainline Tariff	Not specified	Not specified	Not specified	Not specified	Max 3% incl. CO ₂ , N ₂ , He, O ₂	Max 3% by volume
Temperature	Max. 50°C	Max. 49°C	Max. 43.3°C	Max. 49°C	Max. 110°F	Max. 105°F or Min. 50°F	Min 40°F Max 120°F
Heating Value	Min. 36 MJ/m ³ Max, 41.34 MJ/m ³	Min. 36 MJ/m ³	Min. 36 MJ/m ³	Min. 36 MJ/m ³	Min. 995 BTU/ft ³	Min. 990 BTU/ft ³ or Max. 1150 BTU/ft ³	Min. 967BTU/ft ³ Max. 1200 BTU/ft ³
Water	Max. 65 mg/m ³	Max. 65 mg/m ³ or Max. dp -10°C at > 8275 kPa	Max. 65 mg/m ³ or Max. dp -10°C at > 8275 kPa	Max. 65 mg/m ³ or Max. dp -10°C at > 8275 kPa	Max. 4 lbs/MMcf	Max. 7 lbs/MMcf	Max. 7 lbs/MMcf
Hydrocarbon Dewpoint	Max. -10°C at 5500kPa absolute	Max. -10°C at operating pressure	Max. -10°C at operating pressure	Max. -10°C at operating pressure	Max. 15°F up to 800 psig	Max. 20°F up to 600 psig	Max. 15°F
Interchangeability	See TCPL Mainline Tariff	Not Specified	Not Specified	Not Specified	Not Specified	Wobbe Number: Min: 1279 Max: 1385	Not Specified

Canadian Pipelines

Specs	Alliance Canada	Union	Enbridge (Tecumseh Pipeline)	TransGas	West Coast	TQM
Hydrogen Sulphide	Max. 23 mg/m ³	Max. 7 mg/m ³	Max. 7 mg/m ³	Max. 6 mg/m ³	Max. 6 mg/m ³	Max. 23 mg/m ³
Total Sulphur	Max. 115 mg/m ³	Max. 460 mg/m ³	Max. 460 mg/m ³ , 5 mg/m ³ mercaptan	Max. 23 mg/m ³ total, 6 mg/m ³ mercaptan	Max. 23 mg/m ³	Max. 115 mg/m ³
Carbon Dioxide	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume
Oxygen	Max. 0.4% by volume	Max. 0.4% by volume	Max. 0.4% by volume	Max. 0.4% by volume	Max. 0.4% by volume	Max. 0.4% by volume
Nitrogen	Max. 4% by volume incl. N ₂ , CO ₂ , O ₂	Not specified	Not specified	Max. 15 ml/m ³ each (nitric oxide & total oxides of nitrogen)	Not specified	Not specified
Temperature	Max. 50°C, Min. 5°C	Max 43°C	Not specified	Max. 50°C	Max. 54°C	Max. 50°C
Heating Value	Min. 36 MJ/m ³ , Max. 60 MJ/m ³	Min. 36 MJ/m ³ Max. 40.2 MJ/m ³	Min. 36 MJ/m ³ Max. 40.2 MJ/m ³	Min. 35 MJ/m ³	Min. 36 MJ/m ³	Min. 36 MJ/m ³
Water	Max. 65 mg/m ³	Max. 65 mg/m ³	Max. 80 mg/m ³	Max. 65mg/m ³ at 101.325 kPa and 15°C	Max. 65 mg/m ³	Max. 65 mg/m ³
Hydrocarbon Dewpoint	-5°C at normal opt. conditions	Max. -8°C at operating pressure	Max. -10°C at 5500 kPa	Max. -10°C at opt. Pressure	Max. -9°C at del. pres.	Not specified
Interchangeability	Not Specified	Refer to Union Tariff	Refer to Enbridge Tariff	Not Specified	Not Specified	Not Specified

The Gas Quality Specifications tables are intended to be used for planning purposes only and although TransCanada endeavours to maintain the information in such a way that is accurate and current, it may not provide accurate results. Use of this information is at user's sole risk and TransCanada shall not be liable for user's, or any party's, use of or reliance on any results obtained from it.

Website: <http://www.transcanada.com/customerexpress/index.html>

E-mail: customer_express@transcanada.com

The Pipeline: 403.920.PIPE (7473)

November 2016

Gas Quality Specifications

TransCanada and other pipelines



US Pipelines					
Specs	Alliance USA	Empire	GLGT	Iroquois	Northern Border
Hydrogen Sulphide	Max. 1 grains/Ccf	Max. 1 grains/Ccf	Max. 1/4 grains/Ccf	Max. 1/4 grains/Ccf	Max. 0.3 grains/Ccf
Total Sulphur	Max. 5 grains/Ccf	Max. 20 grains/Ccf	Max. 20 grains/Ccf	Max. 1.25 grains/Ccf	Max. 2 grains/Ccf, (0.3 grains mercaptan/Ccf)
Carbon Dioxide	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume	Max. 2% by volume
Oxygen	Max. 0.4% by volume	Max. 1% by volume	Max. 1% by volume	Max. 0.2% by volume	Max. 0.4% by volume
Nitrogen	Not specified	Not specified	Max. 3% by volume	Max. 2.75% N ₂ +O ₂ 4% N ₂ + CO ₂	Not specified
Temperature	Max. 122°F	Max. 120°F, Min. 40°F	Max. 120°F, Min. 20°F	Max. 120°F	Min. 32°F Max. 120°F
Heating Value	Min. 962 BTU/ft ³	Min. 950 BTU/ft ³ Max. 1200 BTU/ft ³	Min. 967 BTU/ft ³ Max. 1069 BTU/ft ³	Min. 967 BTU/ft ³ Max. 1110 BTU/ft ³	Min. 967 BTU/ft ³
Water	Max. 4 lbs/MMcf	Max. 7 lbs/MMcf	Max. 4 lbs/MMcf	Max. 4 lbs/MMcf at 14.73 psi & 60°F	Max. 4 lbs/MMcf
Hydrocarbon Dewpoint	Max. 14°F at opt. pres.	Not specified	Not specified	Max. 15°F or less	Max. -5°F (800psia), -10°F (1000 psia), -18°F at (1100 psia)
Interchangeability	Not specified	Not specified	Not specified	See Iroquois Tariff	Not specified
Specs	NWP	PNGTS	SOCAL	Tennessee GP	Viking
Hydrogen Sulphide	Max. 0.25 grains/Ccf	Max. 0.25 grains/Ccf	Max. 0.25 grains/Ccf	Max. 0.25 grains/Ccf	Max. 1/4 grains/Ccf
Total Sulphur	Max. Non Laplata Facilities 5 grains/Ccf, Laplata Facilities 0.75 grains/Ccf, 0.3 grains mercaptan/Ccf	Max. 20 grains/Ccf	Max. 0.75 grains/Ccf (0.3 grains mercaptan/Ccf)	Max. 10 grains/Ccf	Max. 20 grains/Ccf
Carbon Dioxide	Max. 2% by volume	Max. 3% by volume	Max. 3% by volume	Max. 3% by volume	Max. 3% by volume
Oxygen	Max 0.2% by volume	Max. 0.2% by volume	Max. 0.2% by volume	Max. 0.2% by volume	Max. 0.2% by volume
Nitrogen	Max. 3% incl. O ₂ , CO ₂	Max. 4% incl. CO ₂	Max. 4% incl. O ₂ , CO ₂ and inerts	Max. 4% incl. CO ₂ , O ₂ Max 2.75% N ₂ + CO ₂	Max. 4% incl. CO ₂
Temperature	Non Laplata Facilities Max. 120°F Laplata Min. 40°F, Max. 120°F	Max. 120°F	Min. 50°F, Max. 105°F	Max. 120°F	Max. 120°F
Heating Value	Min. 985 BTU/ft ³	Min. 967 BTU/ft ³ Max. 1100 BTU/ft ³	Min. 990 BTU/ft ³ Max. 1150 BTU/ft ³	Min. 967 BTU/ft ³ Max. 1100 BTU/ft ³	Min. 967 BTU/ft ³ Max. 1100 BTU/ft ³
Water	Max. 7 lbs/MMcf	Max. 7 lbs/MMcf	Max. 7 lbs/MMcf at <800psi or < 20°F at > 800psi	Max. 7 lbs/MMcf at 14.73psi at 60°F	Max. 7 lbs/MMcf at 14.73psi at 60°F
Hydrocarbon Dewpoint	Max. 15°F (100-1000psia)	Not specified	See SOCAL Tariff	Max.15°F	Not specified
Interchangeability	Not Specified	Not Specified	See SOCAL Tariff	See Tennessee GP Tariff	Not Specified

The Gas Quality Specifications tables are intended to be used for planning purposes only and although TransCanada endeavours to maintain the information in such a way that is accurate and current, it may not provide accurate results. Use of this information is at user's sole risk and TransCanada shall not be liable for user's, or any party's, use of or reliance on any results obtained from it.

Website: <http://www.transcanada.com/customerexpress/index.html>
 E-mail: customer_express@transcanada.com
 The Pipeline: 403.920.PIPE (7473)
 November 2016

